



## W3-CD327SIR

High Sensitivity (0.1LUX); Wider Dynamic Range;

Dual Voltage and Lower Power Consumption [ $<1.8W$ ];

Speed White Balance (1FIELD); 540 TVL, Super high resolution;

3 Axis Bracket; SNR (Super Noise Reduction);

IR Function; Waterproof.



### Specification:

<b>Item No</b>	W3-CD327SIR
<b>sensor</b>	1/3 SONY CCD
<b>TV System</b>	PAL/NTSC
<b>Sync</b>	Internal
<b>Resolution</b>	450 Line
<b>S/N ratio</b>	$\geq 50$ dB
<b>Mini Illumination</b>	0.1 Lux(F1.2)
<b>AGC</b>	+18 dB Max
<b>BLC</b>	NO/OFF
<b>AEC</b>	NO/OFF
<b>Mirror</b>	NO/OFF
<b>Voltage</b>	DC 12V
<b>Power Consumption</b>	$<250mA$ (DC 12V)/ $160mA$ (AC 24V)
<b>Lens</b>	3.5~8mm
<b>IR distance</b>	15M
<b>Operation temp</b>	-10 °C To 50 °C (Within85%RH)
<b>Storage temp</b>	-20 °C To 65 °C (Within85%RH)
<b>Dimension</b>	$\Phi 127 \times 93$ mm