



W3-D6109CW, W3-D6116CW



Specification:

Model No.	W3-D6109CW	W3-D6116CW
Video Input	9 CH BNC	16 CH BNC
Video Output	BNC X 2,VGA X 1 (Optional)	
Audio Input/Output	RCA 4-channel / 2-channel	
Compression	Video: H.264 Audio: ADPCM	
Operation Mode	Hexaplex (record, display, playback, backup, operate, remote control)	
Video Record Resolution	(PAL) Display:704x576 Playback:4CH(CIF) 352x288 Half D1:720 x 240 D1:720 x 480	
	(NTSC) Display:720x480 Playback:4CH(CIF) 360x240 Half D1:720 x 288 D1:720 x 576	
Frame Per Second	(PAL) Display:225fps Record:MAX.200 fps(Quad) Each: CIF:22fps/s(Real Time) Half D1:11fps/s D1:5.5fps/s	(PAL) Display:400fps Record:MAX.200 fps(Quad) Each: CIF:12.5fps/s Half D1:6.25fps/s D1:3.125fps/s
	(NTSC) Display: 270fps Record:MAX.240 fps(Quad) Each: CIF:27fps/s(Real Time) Half D1:13fps/s D1:7fps/s	(NTSC) Display: 480fps Record:MAX.240 fps(Quad) Each: CIF:15fps/s Half D1:7.5fps/s D1:3.75fps/s
Live Display	Real Time, Single, Quad	
Video Adjustment	Brightness, Contrast, Color, Watermark	
Alarm Input	9 CH	16 CH
Alarm Output	2 CH	2 CH
Recording Mode	Continuous, Motion Detection, Sensor, Time schedule	
Playback Search	Time, Event(Motion, Alarm)	
Motion Detention	Yes, with configurable detection area & sensitivity	
Video Loss Alarm	Yes	
Remote Controller	Yes	
Network/IP	RJ45	
Pan/Tilt/Zoom	RS485/RS-232	
Restore Configuration after Power Outage	Auto	
HDD storage	Four SATA HDD	
Backup	2 USB 2.0 Ports (Support external DVD-RW, removable HDD) or Internal DVD-RW	
Power Supply	DC 12V/5A	
Weight	14 KG	
Dimension (L x W x H)	540 x 520 x 17mm	
Operating Temperature	-20°C ~ +60°C	