



W3-D8008, W3-D8016



Specification:

Model No.	W3-D8008	W3-D8016
Video Input	BNC X 8	BNC X 16
Video Output	BNC x 1 VGA x 1	
Audio Input/Output	RCA x 8 or No optional	RCA x 16 or No optional
Compression	H.264	
Operation Mode	Triplex	
Video Record Resolution	(PAL) Display:704x576 Playback:8CH(CIF) 352x288 176X144(QCIF)	(PAL) Display:704x576 Playback:16CH(CIF) 352x288 176X144(QCIF)
	(NTSC) Display:720x480 Playback:8CH(CIF) 360x240 160X120(QCIF)	(NTSC) Display:720x480 Playback:16 CH(CIF) 360x240 160X120(QCIF)
Frame Per Second	(PAL) Display:200fps Record:MAX.200 fps(Quad) Each: CIF:1-25fps/s(Real Time)	(PAL) Display:400fps Record:MAX.400 fps(Quad) Each: CIF:1-25fps/s(Real Time)
	(NTSC) Display: 240fps Record:MAX.240 fps(Quad) Each: CIF:1-30fps/s(Real Time)	(NTSC) Display: 480fps Record:MAX.480 fps(Quad) Each: CIF:1-30fps/s(Real Time)
Live Display	Real Time, Single, Quad	
Video Adjustment	Brightness, Contrast, Color, Watermark	
Alarm Input	8 CH	
Alarm Output	4 CH	
Recording Mode	Continue(Manual), Time, Motion Detection(Event),Alarm	
Playback Search	Time, Event(Motion, Alarm)	
Motion Detention	Yes, with configurable detection area & sensitivity	
Video Loss Alarm	Yes	
Remote Controller	Yes	
Network/IP	RJ45	
Pan/Tilt/Zoom	RS422	
Restore Configuration after Power Outage	Auto	
HDD storage	8 pieces of 750 G SATA HDD , up to 6T bytes	
USB backup	Yes	
Power Supply	110~240V ±10%	
Weight	14 KG	
Dimension (L x W x H)	435x465x95mm	
Operating Temperature	-20°C ~ +60°C	