



## ACTO LX 650

 detailed specifications



### Specification

<b>Display Type</b>	0.63" Sony XGA LCD Panels
<b>Resolution</b>	Native XGA (1024 x 768)
<b>Brightness (Typical)</b>	3,200 ANSI Lumens
<b>Contrast Ratio</b>	800:1
<b>Lamp Life and brand</b>	Estimated at 4000/3000 Hours (Eco/Std) 230W NSH USHIO
<b>Throw Ratio</b>	70" @ 2.0 m
<b>Projection Distance</b>	1.0~12.7m
<b>Image Size (Diagonal)</b>	30'~300'
<b>Aspect Ratio</b>	4:3 Native, 16:9 Compatible
<b>Remote Control</b>	IR Remote
<b>Audio</b>	Mono 7-Watt Speaker
<b>Displayable Colors</b>	1.07 Billion
<b>Offset 115% Uniformity</b>	85%
<b>Computer Compatibility</b>	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
<b>Video Compatibility</b>	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i)
<b>Projection Lens</b>	1.2x Manual Zoom and Focus
<b>I/O Connectors</b>	2*VGA-In, VGA-Out, S-Video, Component Video, Audio-Out, RCA (L/R) Audio-Input, RS-232, RJ45, Y/Pb/Pr
<b>Security</b>	Anti-theft Bar, Kensington® Lock Port and Keypad Lock
<b>Projection Method</b>	Front, Rear, Ceiling Mount, Table Top
<b>Weight</b>	3.30kg
<b>Dimensions (W x H x D)</b>	340 x 240 x 90 mm
<b>Noise Level (STD/Bright)</b>	29dB/34dB ±30°
<b>Keystone Correction</b>	Vertical
<b>Horizontal Scan Rate Vertical</b>	15~100 KHz
<b>Refresh Rate</b>	50~100 Hz
<b>Operating Temperature</b>	0°C to 40°C
<b>Power Supply</b>	280W/100 V, 240V @ 50-60Hz
<b>Standard Accessories</b>	Power Cord, VGA Cable, Remote Control, Batteries, Carrying Case, Lens Cap with string, Owner's Manual, Quick Start Card and Warranty Card