



## ACTO LX 660



### Specification:

<b>Native Resolution:</b>	XGA (1024x768)
<b>Compatible Res:</b>	S-video, Composite Video, AV, 15-pin D-Subx2, Mini Jack (Stereo), RCA (L/R) Audio Input
<b>Display Technology:</b>	0.63" LCD
<b>Brightness:</b>	3,800 Ansi lumens
<b>Contrast Ratio:</b>	800:1
<b>Uniformity:</b>	85%
<b>Lamp:</b>	230W NSH / 4, 000 Hrs (ECO), 3, 000 Hrs (Normal)
<b>Lamp Replacement:</b>	Top Cover Drawer Style
<b>Dimension: Net</b>	345mmx245mmx94mm
<b>Weight:</b>	3.20Kg
<b>Performance Noise:</b>	<29dB (ECO)
<b>Projection Method:</b>	Rear/Front/Ceiling
<b>Product Colour:</b>	Pearl white/Silver Grey/Black
<b>Inputs:</b>	S-video, Composite Video, AV, 15-pin D-Subx2, Mini Jack (Stereo), RCA (L/R) Audio Input
<b>Outputs:</b>	15-pin D-Sub, RS232, Mini Jack (Audio Output), RJ45
<b>Video Compatibility:</b>	PAL, SECAM, NTSC 4.43, PAL-M, N, HDTV (480i, 480p, 575i, 575p, 720p, 1035i, 1080i)
<b>Scale Ratio:</b>	4:3 (Standard) / 16:9 (Compatible)
<b>Projector Lens:</b>	F: 2.3~2.5, 1.2x Optic zoom f=18.82~22.60mm 1/4~16 Digital focus function
<b>Digital Keystone Correction:</b>	Vertical $\pm 30^\circ$ Auto Correction
<b>Throw Ratio:</b>	S-video, Composite Video, AV, 15-pin D-Subx2, Mini Jack (Stereo), RCA (L/R) Audio Input
<b>Projection Distance:</b>	1.4m~12.7m
<b>Projection Size:</b>	40"~300" (Diagonal)
<b>H. Scanning Frequency: V.</b>	15~110 KHz
<b>Scanning Frequency:</b>	50~100 Hz
<b>Power Consumption:</b>	310W
<b>Power Supply:</b>	100V - 240V @ 50-60Hz
<b>Speaker:</b>	Mono 7W
<b>OSD Languages:</b>	17 Languages
<b>Standard Accessory:</b>	User Manual, Remote Control, Battery, VGA Cable, Power Cable, Lens Cover, PIN Code Sticker